



Titebond II Premium Wood Glue

Product # 15005004

Volume 16 oz

DESCRIPTION

Titebond II Premium Wood Glue is the only leading single-component wood glue that passes ANSI Type II standards for water resistance. It is ideal for exterior woodworking projects including outdoor furniture, birdhouses, mailboxes, planters, and picnic tables.

Titebond II Premium provides a strong initial tack, fast set speed, superior strength and excellent sandability. It is FDA-approved for indirect food contact (e.g. for cutting boards) and is ideal for radio frequency (R-F) gluing systems.

ADVANTAGES AND BENEFITS

- Designed for exterior use - Excellent sandability - Unaffected by finishes - Ideal for radio frequency (R-F) and hot press gluing systems - FDA approved for indirect food contact - Easy cleanup with water

TECHNICAL SPECIFICATIONS

Product #	15005004
Recommended Use	Interior, Exterior, Cold-Pressed Glue, Indirect Contact with Food
Color Before Application	Cream
Dried Film	Translucent Yellow
Open Time	5 minutes
Close assembly time under pressure	Normal (11-20 min.)
Viscosity	4000 cps
Brand	Titebond®
Features	Water Resistant, Wash with Water
VOC Concentration (EPA Method 24)	5.5 grams per liter
Standards and Certifications	ANSI Type II Water-Resistance, ASTM D-4236, NSF51 Certified for Food Contact
Solid Content (Approx.)	48%
Base	Polyvinyl Acetate
pH	3.0
Freeze/Thaw Stability	Keep From Freezing, Stable

APPLICATION

- Ideal for outside projects - For making butcher blocks

IMPORTANT INFORMATION

- NSF51 certified for food contact - Keep from freezing - Conforms to ASTM D-4236 - First single-component wood glue to meet ANSI Type II water-resistance standards

PRODUCT PHOTOS

