



Jowatherm 286 Hot Melt Adhesive Cartridge

Product # JW28630

Filler Agent Without

Finish/Color Natural

Weight 26 lb

Viscosity 50 000 - 100 000 cps

DESCRIPTION

Hot melt adhesive cartridge with high heat resistance and good cold flexibility.

ADVANTAGES AND BENEFITS

- Excellent color and heat stability - High heat resistance - Good cold flexibility.

TECHNICAL SPECIFICATIONS

Product #	JW28630
Type	Cartridges
Line speed (/minute)	32 ft 9 in to 197 ft*
Adhesive for use with	Thin PVC and ABS edgbanding, Thick PVC and ABS edgbanding, Solid wood edgbanding, Multi-layered 1, 1.5, 2, 3 mm edgbanding, Backed thin wood edgbanding, Laminate, Resin-embedded paper
Working Temperature	180 °C to 200 °C
Brand	Jowat
Features	High Heat Resistance
Base	Ethylene Vinyl Acetate

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Hot melt for automatic edgbanding. Suitable for: - Solid wood - Primed HPL - Veneer - PVC - Resinated paper

IMPORTANT INFORMATION

It is highly recommended to consult your sales representative or a technical expert before purchasing a new edgbanding glue.

PRODUCT PHOTOS

