

PRODUCT TECHNICAL DATA SHEET

D030065 All Purpose Dry Lubricant & Release Agent

DESCRIPTION: The dry lubricant & release agent stops sticking and retards corrosion. This silicone spray eliminates annoying squeaks in hinges, latches, springs, etc. It leaves no greasy or oily film and is not affected by water or oil. The heat stable formula will not freeze or melt.

USES: It protects battery terminals, tools, aluminum windows and doors. An excellent release agent for plastic injection and compression moldings. Use on any surface: metal - glass - rubber - plastic - painted surfaces - fabrics.

SPECS: Can Size: 20 Oz.
Net Weight: 12 Oz.
Shipping Weight: 13 lbs.
Packaged: 12 cans per case

PHYSICAL CHARACTERISTICS: Color: Colorless
Fragrance: Solvent
Shelf Life: 1 Year +

REGULATORY: Ozone Depleting Compounds: None
Recyclable Packaging: Yes
VOC Compliant CARB/OTC: Yes
CPSC Flame Extension: Required to be labeled as extremely flammable per 16 CFR 1500.
DOT Hazard Class: ORM-D
Shipping Name: Consumer Commodity
24 HOUR MEDICAL EMERGENCY: 1-866-836-8855

PRODUCT FEATURES:

- Fast drying
- Leaves no greasy or oily film
- Heat stable - will not freeze or melt
- Use on any surface

