

Mohawk

Finishing Products, Inc.

Product Data Sheet

BACKGROUND BASE COLOR

M104- (COLORS)

AVAILABLE IN 13 oz. AEROSOL

Product Description: Mohawk Background Base Color Aerosols are designed to provide the background colors over a repair on furniture, cabinets or paneling. These background colors are matched to base colors of popular shades in wood tones. The Background Base Color Aerosols are used to cover areas that are in need of repair. Wood graining over base coat colors can be accomplished using Mohawk Nu-Glaze II by brushing or wiping or by using a graining marker. These Background Base Colors are formulated and based on nitrocellulose lacquers, which will not lift when using grainers, glazes or subsequent nitrocellulose topcoats.

Advantages:

1. Easy to use.
2. Made to match background shades of popular wood colors.
3. Solid color - covers completely.

Product Limitations:

1. For interior use only.

Colors Available:

0009 Cream	0018 Light Maple	0019 Fontana Pine
0321 Natural	0328 Light Golden Tan	0357 Medium Brown

Characteristics:

Weight per gallon: 7.72 – 8.03
Flashpoint: <0F/-17.8C
Package Viscosity: 23-25 seconds #1 Zahn cup
Dry time: Air dry @ 72F, 35% RH
To touch: 3 minutes
To handle: 5 minutes
To package: overnight
Volatile Organic Compounds (VOC):
Does not exceed 95%

Spec. Gravity: .93 - .97
Boiling Range: -30F/-34C
Non Volatile (wt): 17.5-21.7%

Package Life: 3 years

Air Quality Data: Non-Photochemically Reactive
*Hazardous Air Pollutants: 0.46 - 0.60 lb./1 lb. solids
* Depending upon color

HMIS:

Health: 1
Flammability: 4
Reactivity: 0
Personal Protection: B

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface should be free of dirt, grease, etc. Use drop cloth or newspapers to protect surrounding areas from spray mist. For best results, use only when can temperature is between 65°F and 90°F.

Spray on a test piece of wood to get the pattern before attempting repair. Spray Background Base Color in short bursts onto the area being repaired. Feather the base coat away from the repaired area thus toning the repair in. Use steady even strokes while spraying. Several thin coats give a better finish than one heavy coat. Allow coating to become tacky between coats.

Complete the repair by matching the existing grain pattern with Mohawk Graining Liquid M403-000 and Blendal Powders or Mohawk Match-All Stain and Grain System, or for large areas use Mohawk Nu-Glaze II M504's for artificial graining. Topcoat repair with Mohawk Tone Finish Clear (M102-0420 to 0422) or Ultra-Flo Clear (M102-0450 to 0452).

For packaging or rubbing, allow at least overnight drying.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.

Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551