



Industrias Químicas Löwenberg, S.L.

Avda. San Pablo, 22
28820 Coslada (Madrid) Spain
Tel: +34 916 278 400 - Fax: +34 916 733 330
E-mail: comercial@quilosa.es



TECHNICAL INFORMATION

QUILOSA. Technical Dept. Edition 1. January 2007

LITEPLAST FIBRE

DESCRIPTION:

Ready-to-use, very easily and quickly applied repair paste, suitable for indoor and outdoor use.

APPLICATIONS:

LITEPLAST FIBRE is a paste to repair and fill cracks and fissures subjected to movement in surfaces of wood, plaster, stucco, or cement and, in general, any porous building material. Substitutes elastic tapes and reinforcing mesh.

PROPERTIES:

LITEPLAST FIBRE is a fibre glass reinforced plaster that does not peel or crack or shrink on drying.

It can replace elastic tape, fibre bands and reinforcing mesh.

High flexibility.

INDICATIONS FOR USE:

Prepare the surfaces, first eliminating dust and loose particles. Slightly dampen the surface to be repaired.

Apply **LITEPLAST FIBRE** with a flexible spatula. Press and smooth the surface by immersing the spatula in water for a good final finish. If necessary to sand, do it when the product is completely dry.

LITEPLAST FIBRE can be painted an hour after it has been applied.

CLEANING:

Work tools can be cleaned with water while the product is soft.

TECHNICAL CHARACTERISTICS:

Appearance	White-coloured paste
Viscosity:	Thixotropic consistency paste.
Density:	(23°C) $0.58 \pm 0.02 \text{ gr/cm}^3$
Solvent:	Water

STORAGE:

Store the product between 5° and 30° C in its original tightly closed container.

Shelf life: at least 24 months in its sealed original containers

PRESENTATION:

Can 750 ml.

HEALTH AND SAFETY:

Harmless product: According to current legislation, it need not carry any indication of risk or safety in its storage or handling.

For further information, request the Safety Data Sheet of the product.

NOTE:

The indications and technical data contained in this data sheet are general, based on our experience and current knowledge. Therefore, if more specific information is required for each product, the product specifications sheet must be requested. Liability cannot be accepted for consequences resulting from improper use and our guarantee is therefore limited exclusively to the quality of the product supplied. This technical sheet may be updated without prior notice (request the latest version as well as the specification sheet in case of need)