

NUOVA S.I.V.A.M. S.p.A.

LZD091	Thinner for PU and ACR products; for basecoats and matt top coats; fast evaporation	SB	870 7.265
LZD092	Thinner for PU and ACR products; for basecoats and matt top coats; medium-fast evaporation	SB	870 7.265
LZD093	Thinner for PU and ACR products; for basecoats and matt top coats; medium evaporation	SB	875 7.307
LZD096	Thinner for PU and ACR products; for basecoats and matt top coats; medium evaporation; extended pot-life	SB	870 7.265
LZD099	Universal thinner, for PU-ACR-NC-EPOX; medium evaporation	SB	870 7.265
LZD100	Retardant thinner anti-foggy, for NC products; also, usable for solvent based stains	SB	900 7.516
LZD101	Retardant thinner for PU and ACR; slow evaporation	SB	960 8.017
LZD102	Retardant universal thinner for PU-ACR-NC; slow evaporation; also, usable for solvent based stains	SB	920 7.683
LZD183	Thinner for glossy PU and ACR; medium-slow evaporation; aromatic free	SB	880 7.349
LZD429	Thinner for water based wood impregnating; slow evaporation; to be used only in summer period	WB	1040 8.685
LZD441	Thinner for PU and ACR; basecoats and matt top coats; fast drying; aromatic free	SB	810 6.764
LZD442	Thinner to improve wetting for PU and ACR; medium evaporation; aromatic free	SB	804 6.714
LZD446	Reactive thinner for polyester products, redox drying	SB	905 7.557
LZD450	Thinner for water based products, interior and exterior; slow evaporation; to be used only in summer period	SB	900 7.516
LZD475	Universal thinner, for PU-ACR-NC; basecoat and matt top coats; fast evaporation; aromatic free	SB	900 7.516
LZD484	Retardant thinner for glossy PU and ACR; high wetting; slow evaporation	SB	950 7.933
LZD786	Universal thinner for water based products; basecoats and top coats; interior and exterior	WB	965 8.058
LZD888	Washing thinner for WB products; it can be used only for washing, not to dilute the WB products	WB	990 8,267

STORAGE: Keep in a fresh and well-ventilated place; preferably not exceed 30°C/86°F.



NUOVA S.I.V.A.M. S.p.A.

TDs LZD xxx (series) – 2017, November – revision NA02

IMPORTANT: The information contained in this technical data sheet are based on the average results obtained in our laboratories and is the best experience we have acquired in the most rigorous manner, thorough tests and checks.

Nuova S.I.V.A.M. guarantees the consistency of the chemical/physical characteristics of its products within the tolerances indicated above.

The final result is the full responsibility of the user who, before using the product, must check that it meets his requirements in terms of safety, application equipment, support material to paint, and environmental conditions.

The information given herein is based on a temperature of 20°C/68°F and 70% of relative humidity.

Nuova S.I.V.A.M. technical and commercial network is at your complete disposal to deal with any questions regarding how to correctly apply and use our products.