



## FlexyLED LED Tape HE CR 24 V

Product # 107024124119

**Light Color** Neutral White

Kelvin Color Temperature (K) 4250 K - 4600 K

Length 9 ft 10 in\*

**Watts** 28.8 W

Luminous Flux 2478 Lumen

#### **DESCRIPTION**

9.6 W/m power, with IP44 rating

- Resin silicone-coated material that protects the LED strip from dust, moisture, and water splashes.
- An innovative quick-plug system designed for connecting modules of different lengths in a continuous row while maintaining the distance between the LED lights and ensuring a perfectly uniform light distribution.

#### **ADVANTAGES AND BENEFITS**

- Flexible LED tape available in different lengths. Can be cut every 2 in (50 mm) or six LED lights. Quick connect system, no soldering of wires. The highly resistant double-sided adhesive provides fast installation without the use of any tools. The resin protects each LED strip against moderate mechanical shock and water splashes.
- Compatible dimmer switches available (see Suggested Products).



# REQUIRED PRODUCTS

Requires the following products



24 V X-DRIVER

Requires ONE of the following products

Sales unit



2 m (6 ft 6") Power Cable for LED Flexyled HE CR 24 V Tape Product # 107024079





Connecting Cable for LED 24V Tape Product # 107024020



### **TECHNICAL SPECIFICATIONS**

Product #	107024124119
Location	Under Cabinet, Countertop, Baseboard
Application	Kitchen, Bedroom, Commercial, Closet
Mounting	Recessed, Surface
Luminaire	Flexible Linear
Compatibility	Micro 24
Lighting	Accent, Task
Standards and Certifications	cULus
CRI (Color Rendering Index)	80
Luminous Efficiency	85 lm/W
Height	5/32 in*
Width	5/16 in*
IP	IP44
Lighting Type	LED
Tension (V)	24 V
Group	LED Group A
Connection Type	Micro 24

#### **Disclaimer**

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

### IMPORTANT INFORMATION

- Tapes can be connected to one another to reach a maximum length of 235 in (5969 mm) - 120 LED/meter modules - Power cord required and sold separately (see Suggested Products) - Connecting cable sold separately (see Suggested Products)

# **INCLUDED PRODUCT(S)**

- FlexyLED CR tape light with 3MTM adhesive tape

### **APPLICATION**

- Kitchen - Toe kick - Bathrooms



### **DISCLAIMER**

- Product information subject to change without notice. - There is no replacement bulb available for this light due to its average lifespan of 50 000 hours. - Richelieu grants no warranty on LED lights if a power supply other than the one specifically prescribed for this product is used. - Do not exceed the maximum wattage by connecting more lights than prescribed; damage to the power supply may result. - Wattage calculation for power supplies should be using an 80% maximum yield. - Do not make the LED strip turn on itself. - Do not bend LED strip. - Power cord required and sold separately available in 79 in (2 m) length (please see Suggested Products). - 1 31/32 in (50 mm) connecting cable sold separately (please see Suggested Products). - Please contact the special orders desk for any special requests.

### **PRODUCT PHOTOS**





