

## Pocket/Pocketless Door Hardware Kit

**Product #** 148075BC

### DESCRIPTION

For one sliding pocket door with a thickness from 3/4 in (19.05 mm) to 1 3/4 in (44.45 mm) and weighing up to 75 lb (34 kg) for a maximum 36" (914.4 mm) finished opening. Jump-proof V-shaped track is constructed of corrosion-resistant galvanized steel. Adjustable locking hangers lock in one easy motion and allow up to 5/8" (15.87 mm) of vertical adjustment.

### ADVANTAGES AND BENEFITS

For one sliding pocket door with a thickness of 3/4 in (19.05 mm) to 1 3/4 in (44.45 mm) and weighing up to 75 lb (34 kg) for a maximum 36 in (914.4 mm) finished opening. Jump-proof V-shaped track is constructed of corrosion-resistant galvanized steel. Adjustable locking hangers lock in one easy motion and allow up to 5/8 in (15.87 mm) of vertical adjustment.

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	148075BC
<b>Door Material</b>	Wood
<b>Door Thickness</b>	3/4 to 1 3/4 in
<b>Finish</b>	Zinc Plated, Zinc
<b>Depth</b>	2 in
<b>Packaging Format</b>	White Cardboard with Photo Label
<b>Load Capacity</b>	Max. 75 lb*
<b>Product type</b>	Hardware for Bypassing Doors
<b>Overall Length</b>	72 in
<b>Manufacturing Material</b>	Steel
<b>Door Width</b>	Max. 36 in
<b>Number of Doors</b>	1
<b>Door Position</b>	Concealed Inside Wall
<b>Roller Type</b>	Axle (Bushing)
<b>Roller Position</b>	Upper
<b>Door Movement</b>	Straight Sliding
<b>Track Mounting</b>	Ceiling Mount
<b>Application</b>	Closet and Walk-In Closet, Storage, Pocket Door
<b>Overall Height</b>	1 in

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

Each kit includes 1 track, 2 door hangers, 1 wall-mounted door bumper (for pocket door), 1 floor-mounted bumper (for pocketless door), 1 set of wall/floor glides, and all necessary screws for mounting. Door panel, casings, and trim are not included.

## IMPORTANT INFORMATION

Do not exceed safe working load.

## PRODUCT PHOTOS

