



Titebond III Ultimate Wood Glue

Product # 15001416

Volume 1 gal.

DESCRIPTION

A revolutionary technology offering the best performance in wood adhesives. Meets ANSI/HPVA Type I water-resistance standards and offers superior bond strength, longer open assembly time, and a lower application temperature.

Safer to use than traditional waterproof wood glues, Titebond III is non-toxic, solvent-free, and cleans up with water. Provides strong initial tack, sands easily without softening, and is FDA approved for indirect food contact (e.g. cutting boards). The ultimate in wood glues, ideal for both interior and exterior applications.

ADVANTAGES AND BENEFITS

- Waterproof formula that cleans up with water - Superior strength - Strong initial tack - Designed for interior and exterior applications - Longer open assembly time - Lower application temperature - Unaffected by finishes

TECHNICAL SPECIFICATIONS

| | |
|---|--|
| Product # | 15001416 |
| Recommended Use | Interior, Exterior, Indirect Contact with Food |
| Color Before Application | Tan |
| Dried Film | Light Brown |
| Open Time | 6 to 10 minutes |
| Close assembly time under pressure | Normal (11-20 min.) |
| Viscosity | 4200 cps |
| Brand | Titebond® |
| VOC Concentration (EPA Method 24) | 5.6 grams per liter |
| Standards and Certifications | ASTM D-4236, ANSI/HPVA Type I Water-Resistance |
| Solid Content (Approx.) | 52% |
| Base | Advanced Proprietary Polymer |
| pH | 2.5 |
| Freeze/Thaw Stability | Keep From Freezing, Stable |

APPLICATION

- Ideal for wood projects - Indoor and outdoor applications

IMPORTANT INFORMATION

FDA approved for indirect food contact Conforms to ASTM D-4236 Complies with ANSI/HPVA Type I water-resistance standards

PRODUCT PHOTOS

