



Titebond II Fluorescent Wood Glue

Product # 15002317

DESCRIPTION

Titebond II Fluorescent can help any woodworker achieve professional-looking results. Provides a strong initial tack and fast set speed to reduce clamp time. Develops bonds stronger than wood, offers excellent sandability, and is unaffected by finishes.

Titebond II Fluorescent contains a dye that, when viewed under a black light, enables woodworkers to inspect the glue line and assist in the cleanup process. Easy to use, ideal for most porous materials, and cleans up with water.

ADVANTAGES AND BENEFITS

- Visible under black light, enabling detection and removal of dried glue before finishing
- Versatile: bonds wood, hardboard, high pressure laminates and particleboard
- Excellent heat and solvent resistance
- Fast-setting, shortening clamp time
- Ideal for radio frequency (R-F) gluing systems
- Easy cleanup with water

TECHNICAL SPECIFICATIONS

Product #	15002317
Recommended Use	Interior, Exterior, Laminates, Hot Pressing
Color Before Application	Cream
Dried Film	Translucent Yellow
Open Time	5 minutes
Close assembly time under pressure	Normal (11-20 min.)
Viscosity	4000 cps
Volume	5 gal.
Brand	Titebond®
Features	Solvent Resistant, Fast Setting, Fluorescent, High Heat Resistance, Wash with Water
VOC Concentration (EPA Method 24)	5.5 grams per liter
Standards and Certifications	ANSI Type II Water-Resistance
Solid Content (Approx.)	48%
Base	Cross-linking Polyvinyl Acetate
pH	3.0
Freeze/Thaw Stability	Keep From Freezing, Stable

IMPORTANT INFORMATION

- Passes ANSI Type II water resistance

PRODUCT PHOTOS

