



Titebond II Dark Wood Glue

Product # 15003706

DESCRIPTION

Titebond II Dark Wood Glue is a dyed version of Titebond II Wood Glue. Used by professional woodworkers, this single component glue was designed for both interior and exterior projects. Offers a strong initial tack, excellent sanding, and is unaffected by finishes.

ADVANTAGES AND BENEFITS

- Designed for interior and exterior applications - Excellent sandability - Unaffected by finishes - Ideal for radio frequency (R-F) gluing systems - Easy cleanup with water

TECHNICAL SPECIFICATIONS

Product #	15003706
Recommended Use	Interior, Exterior
Color Before Application	Light Brown
Dried Film	Brown
Open Time	1 to 5 minutes
Close assembly time under pressure	Very Long (30 min.)
Viscosity	3200 cps
Volume	1 gal.
Brand	Titebond®
Standards and Certifications	ANSI Type II Water-Resistance, ASTM D-4236
Solid Content (Approx.)	48%
Base	Cross-linking Polyvinyl Acetate
pH	3.0
Freeze/Thaw Stability	Keep From Freezing, Stable

APPLICATION

Ideal for wood, hardboard, particleboard, leather, cloth, and most other porous materials.

IMPORTANT INFORMATION

KEEP FROM FREEZING - Conforms to ASTM D-4236 - Passes ANSI Type II water-resistance

PRODUCT PHOTOS

