



Titebond Doweling Glue - Very Low Viscosity

Product # 15003817

DESCRIPTION

Titebond Doweling Glue with very low viscosity (140 cps) is designed to facilitate flow through the tubes and narrow dowels injectors. This glue hardens quickly to reduce assembly time and provides excellent strength. Its invisible seal ensures a professional finish.

ADVANTAGES AND BENEFITS

- Fast setting - Reduced clamping time - Superior strength - Excellent sanding - Unaffected by finishes - Easy to clean with water

TECHNICAL SPECIFICATIONS

| | |
|--|----------------------------|
| Product # | 15003817 |
| Recommended Use | Interior, Dowel Glue |
| Color Before Application | White |
| Dried Film | Translucent |
| Open Time | 1 to 5 minutes |
| Viscosity | 140 cps |
| Volume | 5 gal. |
| Brand | Titebond® |
| Features | Fast Setting |
| VOC Concentration (EPA Method 24) | 9.6 grams per liter |
| Solid Content (Approx.) | 44% |
| Base | Polyvinyl Acetate Emulsion |
| pH | 4.7 |
| Freeze/Thaw Stability | Unstable |

APPLICATION

Use on wood, hardboard, particleboard, leather, cloth, and other porous materials.

IMPORTANT INFORMATION

- Keep from freezing. - For use with European-made doweling equipment.

PRODUCT PHOTOS

