



## Titebond Original Wood Glue

**Product #** 15005067

**Volume** 5 gal.

### DESCRIPTION

Titebond Original Wood Glue is the industry standard for woodworking. With a strong initial tack and fast set speed to reduce clamp time, this glue develops a bond stronger than the wood itself. Offers excellent sandability and is unaffected by finishes.

Titebond Original can help any woodworker achieve professional-looking results. Ideal for wood, hardboard, particleboard, leather, cloth, and most other porous materials. Titebond Original is non-toxic, easy to use, and cleans up with water.

### ADVANTAGES AND BENEFITS

- Fast setting to shorten clamp time - Bonds stronger than wood - Excellent heat and solvent resistance - Excellent sandability - Unaffected by finishes - Versatile: bonds wood, hardboard, high pressure laminates and particleboard - Easy clean-up with water

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	15005067
<b>Recommended Use</b>	Interior, General-Use Glue
<b>Color Before Application</b>	Yellow
<b>Dried Film</b>	Translucent
<b>Open Time</b>	1 to 5 minutes
<b>Viscosity</b>	3200 cps
<b>Brand</b>	Titebond®
<b>Features</b>	Solvent Resistant, Fast Setting, High Heat Resistance
<b>VOC Concentration (EPA Method 24)</b>	10.7 grams per liter
<b>Standards and Certifications</b>	CARB, ASTM D-4236
<b>Solid Content (Approx.)</b>	46%
<b>Base</b>	Aliphatic Resin Emulsion
<b>pH</b>	4.6
<b>Freeze/Thaw Stability</b>	Keep From Freezing, Stable

### APPLICATION

All common wood species, particleboard, MDF, plywood, and other porous materials.

### IMPORTANT INFORMATION

- Conforms to ASTM D-4236 - Within the formaldehyde limits set by the California Air Resources Board (CARB)

---

**PRODUCT PHOTOS**

