



FlexyLED UHE6B PW 24 V

Product # 1670242012279

Light Color Warm White

Kelvin Color Temperature (K) 3000 K

LED Strip Length 78 3/4 in*

Watts 20 W

DESCRIPTION

Ultra high emitting LED tape

- FlexyLED UHE6B PW is a LED strip with 280 LED/m on a circuit 1/4 in (6 mm) wide.
- Pre-wired collection features modules with varying lengths.
- Supplied with power cable, and ready to be installed without the need for complicated soldering.
- Supplied with a high adherence 3M adhesive.

ADVANTAGES AND BENEFITS

- Surface or integrated into profiles - Reinforced solder power supply cable terminals - Can be cut every 1 in (25 mm) - Compatible with Apex, Miss, and Lab - 10 W/m - 280 LEDs/meter



REQUIRED PRODUCTS

Requires the following products



24 V X-DRIVER

Requires ONE of the following products



Blade-In Profile



Blade Surface Profile

OR



TECHNICAL SPECIFICATIONS

Product # 1670242012279 Location Inside Cabinet, Under Cabinet, Furniture Application Kitchen, Office, Furniture, Closet Mounting Surface Luminaire Flexible Linear Compatibility Micro 24 Lighting Ambience, Accent Style Contemporary CRI (Color Rendering Index) 80 Luminous Efficiency 82 Im/W Power Cable Length 78 3/4 in* IP IP20 Lighting Type LED Tension (V) 24 V Group LED Group A Power Cable Double		
Application Kitchen, Office, Furniture, Closet Mounting Surface Luminaire Flexible Linear Compatibility Micro 24 Lighting Ambience, Accent Style Contemporary CRI (Color Rendering Index) 80 Luminous Efficiency 82 Im/W Power Cable Length 78 3/4 in* IP IP20 Lighting Type LED Tension (V) 24 V Group LED Group A	Product #	1670242012279
MountingSurfaceLuminaireFlexible LinearCompatibilityMicro 24LightingAmbience, AccentStyleContemporaryCRI (Color Rendering Index)80Luminous Efficiency82 Im/WPower Cable Length78 3/4 in*IPIP20Lighting TypeLEDTension (V)24 VGroupLED Group A	Location	Inside Cabinet, Under Cabinet, Furniture
Luminaire Flexible Linear Compatibility Micro 24 Lighting Ambience, Accent Style Contemporary CRI (Color Rendering Index) 80 Luminous Efficiency 82 Im/W Power Cable Length 78 3/4 in* IP IP20 Lighting Type LED Tension (V) 24 V Group LED Group A	Application	Kitchen, Office, Furniture, Closet
Compatibility Lighting Ambience, Accent Style Contemporary CRI (Color Rendering Index) Luminous Efficiency 82 Im/W Power Cable Length 78 3/4 in* IP IP20 Lighting Type LED Tension (V) 24 V Group Light Group A	Mounting	Surface
Lighting Ambience, Accent Style Contemporary CRI (Color Rendering Index) 80 Luminous Efficiency 82 Im/W Power Cable Length 78 3/4 in* IP IP20 Lighting Type LED Tension (V) 24 V Group LED Group A	Luminaire	Flexible Linear
StyleContemporaryCRI (Color Rendering Index)80Luminous Efficiency82 lm/WPower Cable Length78 3/4 in*IPIP20Lighting TypeLEDTension (V)24 VGroupLED Group A	Compatibility	Micro 24
CRI (Color Rendering Index) 80 Luminous Efficiency 82 lm/W Power Cable Length 78 3/4 in* IP IP20 Lighting Type LED Tension (V) 24 V Group LED Group A	Lighting	Ambience, Accent
Luminous Efficiency82 Im/WPower Cable Length78 3/4 in*IPIP20Lighting TypeLEDTension (V)24 VGroupLED Group A	Style	Contemporary
Power Cable Length 78 3/4 in* IP IP20 Lighting Type LED Tension (V) 24 V Group LED Group A	CRI (Color Rendering Index)	80
IP IP20 Lighting Type LED Tension (V) 24 V Group LED Group A	Luminous Efficiency	82 lm/W
Lighting Type LED Tension (V) 24 V Group LED Group A	Power Cable Length	78 3/4 in*
Tension (V) 24 V Group LED Group A	IP	IP20
Group LED Group A	Lighting Type	LED
	Tension (V)	24 V
Power Cable Double	Group	LED Group A
	Power Cable	Double
Connection Type Micro 24	Connection Type	Micro 24
Brand 3M	Brand	3M
Features Dimmable	Features	Dimmable
Length of second power cable 78 3/4 in*	Length of second power cable	78 3/4 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

INCLUDED PRODUCT(S)

- 78 23/32 in (2000 mm) cable



PRODUCT PHOTOS



