

type

В



Product # 189BEMTYPB

Door Installation Left and right hand

Compatible with PS48 / PS40

Load Capacity 30 to 80 kg

Door Thickness 18 to 53 mm

Door Width 1 154 to 1 900 mm

#### DESCRIPTION

#### Electric motor for sliding doors

The B-Moved Motion Transmission Bar is an electric motor engineered to move sliding doors for the systems PS40, PS48, and PS66. Select from four types of motion transmission bars. Base your selection first on the compatibility of the sliding system and then on door width. The motion transmission bar mounts within the PS66 sliding mechanisms and to an upper aluminum profile on top of the cabinet and behind the track for the PS40 and PS48 systems. Note to plan for extra depth to fit the motion transmission bar as per the instructions. A connector bracket set connects the PS40 and PS48 to the motion transmission bar. For the PS66, the connector bracket is included.

IMPORTANT: Use metric dimensions for greater accuracy during installation.

# **ADVANTAGES AND BENEFITS**

 $^{\ast}$  Compatible with PS40, PS48, and PS66 sliding door systems  $^{\ast}$  Concealed Motor  $^{\ast}$  Smooth Running

# **TECHNICAL SPECIFICATIONS**

Product #	189BEMTYPB
Product type	Mounting Accessories
Door Material	Wood, Glass
Door Height	1 000 to 3 000 mm
Number of Doors	1
Brand	CINETTO
Brand Model	Cinetto B-Moved

# APPLICATION

Wardrobe, Storage, Furniture, Armoire, Bookshelf

# **INCLUDED PRODUCT(S)**

1 transmission bar



### **IMPORTANT INFORMATION**

Select the correct transmission bar for the appropriate system and door width. Use metric dimensions for greater accuracy during installation. Please make sure to read the entirety of the installation manual before proceeding with the installation. Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. Never spray lubricant on this product. Do not exceed stated limitations and parameters. This will cause early wear and performance failure.

### DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

### PRODUCT PHOTOS

