



SLIDE 25 Single Recessed Track

Product # 189RS836L210

Overall Length 78 3/8 in*

DESCRIPTION

Press fit

Recess mount aluminum single track for the SLIDE 25 sliding door system. Available in two lengths: 78 1/4 in (1.99 m) and 117 5/8 in (2.99 m).

Cut groove 13/32 in (10 mm) wide x 7/32 in (5.5 mm) deep. Use metric dimensions for greater accuracy during installation.

TECHNICAL SPECIFICATIONS

| Product # | 189RS836L210 |
|------------------------|--------------------------------|
| Track type | Single Running, Single guiding |
| Load Capacity | 55.1 lb* |
| Manufacturing Material | Aluminum |
| Track Mounting | Recessed - Inside Ceiling |
| Width | 21/32 in* |
| Finish | Anodized |
| Door Material | Aluminum/Metal Frame, Wood |
| Pre-drilled | No |
| Door Movement | Straight Sliding |
| Door Thickness | 19/32 to 31/32 in* |
| Product type | Running and Guiding Tracks |
| Overall Height | 1/4 in* |
| Application | Furniture, Cabinet, Storage |

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

IMPORTANT INFORMATION

- Use metric dimensions for greater accuracy during installation. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure.



DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

