



AVENTOS HK top Mechanism

Product # 22K2500

LF Power factor 930-2800

DESCRIPTION

Linear design

AVENTOS HK top blends discreetly into top wall cabinets, thus placing even greater focus on the design of the furniture. The size of AVENTOS HK top makes it ideal for small cabinets. This compact yet powerful fitting is even suitable for large wall cabinets. The opening angle stop is already integrated with AVENTOS HK top. The opening distance of the front is infinitely variable and can therefore be set exactly as required.

ADVANTAGES AND BENEFITS

An innovative mechanism prevents the lever arm from folding out unintentionally. This helps ensure safe installation. Adjust the lift mechanism precisely to the weight of the front and the stay lift remains exactly where you want it to, meaning it is always easy to reach. Two different lift mechanisms are available: with positioning template or with pre-mounted system screws (reversible). AVENTOS HK top offers many opportunities for creating a space that's even more unique.

REQUIRED PRODUCTS

Requires the following products



AVENTOS HK top mechanism cover

Requires ONE of the following products

Sales unit



AVENTOS HS/HL/HK Front Fixing Bracket for Thin Fronts
Product # 20S42T1

OR



AVENTOS HS/HL/HK et HK top Hardware Set for Narrow Aluminum Frames
Product # 20S4200A

OR



Hardware Bracket Set for Wood and Wide-Framed Aluminum Doors
Product # 20S4200

Pair

TECHNICAL SPECIFICATIONS

Product #	22K2500
Load Capacity	Max. 39.7 lb*
Screw/Nail	Positioning Template
Brand	Blum
Side	Both
Mechanism Strength	Heavy Weight
Door Height	8 1/16 to 23 5/8 in*
Material	Steel
System Type	Arm
Door Length	Max. 70 7/8 in*
Minimum internal depth of the enclosure	7 3/8 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

For door thicknesses up to 30 mm Distinctive style in cabinet interior Unrestricted range of motion Ample storage space Enhanced ease of use

INCLUDED PRODUCT(S)

HK top with pre-mounted system Euro screws are reversible (four drill holes in the 32 mm system are required). HK top with the positioning template are not reversible (no pre-drilling necessary).

IMPORTANT INFORMATION

Please consult the supplier's documents in order to properly calculate the Power factor (LF) required for your project. Always round up to the highest number for your selection. Formula: (LF) = Cabinet height (KH) mm x Front weight including double handle weight (kg) Blum recommends using a torque screwdriver. This type of screwdriver is not available yet from Richelieu.

DISCLAIMER

Max. front weight 18 kg for two lift mechanisms. Opening angle: LF of 420 to 2800 107° LF of 1730 to 9000 100°

PRODUCT PHOTOS

