



Industrial - Decorative Visible Rail System

Product # 2460120SSPVC

DESCRIPTION

Interior Barn Door

The Industrial Barn Door Style sliding door kit with 2.0 m (78") upper track in stainless steel. The kit is made for door thickness of 35 to 45 mm (1 3/8" to 1 3/4"). The lag bolt and pre-drilled track makes for a simple installation

This is an economical product intended for residential light duty use. Not recommended for high traffic commercial and hotel applications.

Please refer to the ALBERGO series for commercial and hotel applications.

ADVANTAGES AND BENEFITS

Ball bearings for easy movement. Security: The system is equipped with an anti-derailment device for each bearing support to prevent the door from stalling when misused.

TECHNICAL SPECIFICATIONS

Product #	2460120SSPVC
Door Material	Wood
Door Movement	Straight Sliding
Track Mounting	Wall Mount
Load Capacity	33.1 to 176 lb*
Door Position	In Front of Wall
Door Thickness	1 3/8 to 1 3/4 in
Roller Type	Ball Bearing
Roller Position	Upper
Application	Closet and Walk-In Closet, Standard Access Door, Barn Door
Brand	Onward
Screw/Nail Included	Yes
Height Clearance	4 11/32 in*
Overall Length	78 3/4 in*
Packaging Format	Complete Kit
Track type	Tube
Running Track Fixing	Surface Mount
Manufacturing Material	Stainless Steel
Finish	Stainless Steel (170)
Soft-Closing	No

Soft-Close Type	None
Stopper	Two
Product type	2 m Kit
Style	Contemporary
Groove Depth	25/32 in*
Groove Needed for Guiding System	No
Door Projection	2 23/32 in*
Number of Doors	1
Door Height	96 in*
Door Width	24 to 40 in
Groove Width at the Bottom of Door	9/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Interior access door

INCLUDED PRODUCT(S)

1 two-meter rail (tube) 2 single roller supports 2 bumpers 4 wall mounting brackets 1 door bottom guide Screws are included

IMPORTANT INFORMATION

Door and door handle not included. To reduce operating noise, use a door that is heavier than the minimum weight: a solid wood door or a glass door is recommended. For privacy, it is best to use a door that is wider than the door opening. For example, a door 34" wide door is recommended for a 30" opening. The bottom of the door requires a groove for the concealed guiding system. Preparation: Remove the moldings or install a piece of wood (not included) of the same length and thickness before setting the new hardware in place. This is to check door clearance. Ensure product is properly anchored/installed using anchors that are appropriate for the supporting material. Extra anchors that may be required are sold separately. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

