



Traditional - Decorative Concealed Rail System

Product # 2460502MDFPVC

DESCRIPTION

Interior Barn Door

The Traditional is a concealed wall mount sliding door kit for one wood door running on a box track with clip-on wood (MDF) fascia for a single wood door weighing up to 88 lb (40 kg).

Features:

- Kit format includes hardware set for one door, track, and clip-on wood fascia 78 in (2 m) long
- Two-part floor guide that does not require a groove
- Includes two soft-close mechanisms

The Traditional is an ideal solution for residential applications.

ADVANTAGES AND BENEFITS

- Integrated soft-close system at both ends.
- Ball bearings for easy movement.
- Mounting rail pre-drilled every 450 mm (17-23/32") for wall installation.
- Rail can be cut using proper tools (e.g. miter saw with blade for nonferrous metals). It's important to note that each end must be cut in equal parts to maintain the layout of the drilled rail.

TECHNICAL SPECIFICATIONS

Product #	2460502MDFPVC
Door Material	Wood
Door Movement	Straight Sliding
Track Mounting	Wall Mount
Load Capacity	33.1 to 88.2 lb*
Door Position	In Front of Wall
Door Thickness	1 3/8 to 1 3/4 in
Roller Type	Ball Bearing
Roller Position	Upper
Application	Closet and Walk-In Closet, Standard Access Door
Brand	Onward
Screw/Nail Included	Yes
Height Clearance	4 11/32 in*
Overall Length	78 3/4 in*
Packaging Format	PVC and Clear Foam
Track type	Box Track
Running Track Fixing	Surface Mount
Manufacturing Material	Aluminum

Finish	Unfinished, Satin Aluminum
Soft-Closing	Yes
Soft-Close Type	Two-Way Operation
Soft-Close Direction	Opening
Product type	2 m Kit
Style	Contemporary
Groove Needed for Guiding System	No
Door Projection	3 3/8 in*
Door Installation	Top Hung
Number of Doors	1
Door Height	96 in*
Door Width	24 to 36 in

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Interior door.

INCLUDED PRODUCT(S)

- 1 two-meter (6' 6") ball bearing rail pre-drilled every 450 mm (17-23/32") - 3 mounting pieces for the finishing band - 1 two-meter MDF finishing band - 2 MDF end caps - 2 carriages with 4 wheels and mounting plate - 2 soft-close mechanisms - 1 guide - Screws

IMPORTANT INFORMATION

Door handles and door not included. It is recommended to use a solid or glass door in order to obtain the minimum weight to reduce noise resonance. Use a wider door opening to avoid angled views and preserve privacy. It is recommended to use a door 863.6 mm (34") wide for an opening of 762 mm (30"). The bottom of the door requires a groove for the concealed guiding system. Preparation: Remove the frame moldings or install a piece of wood (not included) of the same thickness and length before setting the new hardware in place to ensure the release of the door. Always make sure that the product is properly attached or installed using appropriate fixings material. An additional anchor may be required for installation (sold separately). - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

