



## Tube Pull Handle - One Side with Caps

**Product #** 246207002592170

**Color/Finish** Stainless Steel

### DESCRIPTION

#### For swing and sliding doors

The Tube Pull Handle with one side mounting and cover caps for through bolt fasteners is designed for a wood door. Includes two through bolt fasteners for wood door thicknesses of 1 3/8 in (35 mm) to 1 9/16 in (40 mm). A series of washers and rosettes help to resist compression and damage to the surface of the door when installed. Select from two different finishes that match our collection of decorative barn door sliding kits in brushed stainless steel and matte black. See the Suggested Products below to explore a list of popular decorative barn door sliding kits and systems. The Tube Pull handle has a comfortable and secure grip for both residential and commercial interior door applications for swing, pivot, and sliding wood doors. Ideal for bathrooms, home offices, bedrooms, boardrooms, and meeting rooms. For an installation tip, pre-drill holes carefully for the through bolts from both surfaces of the door to avoid material blow out.

### ADVANTAGES AND BENEFITS

Can be used for swing, pivot, and sliding doors. Two different finishes that match and complement the standard selection of barn door sliding systems. Washers and rosettes help to resist compression and damage to the surface of the door when installed. Cover caps for through bolts. Comfortable and secure grip.

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	246207002592170
<b>Door Type</b>	Wood
<b>Door Thickness</b>	1 3/8 to 1 9/16 in*
<b>Function</b>	Single Pull Handle, Passage
<b>Usage</b>	Sliding Door
<b>Screw</b>	Included
<b>Length</b>	19 3/4 in*
<b>Projection</b>	2 5/16 in*
<b>Material</b>	Steel
<b>Brand</b>	Onward
<b>Center to Center Drilling (Spacing)</b>	11 3/4 in*
<b>Edge Distance</b>	3 15/16 in*
<b>Milling Dimension</b>	1/4 in*
<b>Diameter</b>	3/4 in*

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

- 2 door pulls - 2 rosettes and washers - 2 through bolts for door thickness of 1 3/8 in (35 mm) to 1 9/16 in (40 mm) - 2 cover caps

## IMPORTANT INFORMATION

**IMPORTANT:** Designed for interior wood doors, not suitable for exterior applications. - Please make sure to read the entirety of the installation manual before proceeding with the installation - Pre-drill for through bolts - Do not overtighten fasteners - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection - Do not use abrasive cleaners

## DISCLAIMER

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris, dust, or residues (sawdust or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product.

## PRODUCT PHOTOS





