



Flat Bar Door Handle with Round Disc Pull

Product # 2462070200160

Color/Finish Satin Brass

Material Stainless Steel 304

DESCRIPTION

Low profile round disc pull

Flat Bar Door Handle with through bolt fasteners with one low profile round pull and one cover cap for the opposite side of the door. Includes two sets of through bolt fasteners for various wood door thicknesses: 1 3/8 to 1 3/4 in (35 to 45 mm) and 1 3/4 to 2 1/8 in (45 to 55 mm). Select from four different finishes that match our collection of Decorative Flat Bar Barn Door Sliding kits in satin brass, brushed stainless steel, matte black, and brushed oil-rubber bronze. See the Suggested Products below to explore a list of popular Decorative Barn Door Sliding kits and systems. The flat bar pull handle is secure and robust to grip and the low profile round disc pull on the opposite side does not protrude out far and stays within the gap between the back of the door and the wall. Ideal for both residential and commercial applications for sliding doors.

ADVANTAGES AND BENEFITS

For a wide range of door thicknesses from 1 3/8 in (35 mm) to 2 1/8 in (55 mm). Four different finishes that match and are complementary to the standard selection of barn door sliding systems. Low profile round disc pull on the back of the door fits within the gap between the door and the wall for a barn door sliding system. Secure grip.

TECHNICAL SPECIFICATIONS

Product #	2462070200160
Door Type	Wood
Door Thickness	1 3/8 to 2 5/32 in*
Thickness	1/4 in*
Function	Passage
Usage	Pocket Door, Sliding Door
Width	1 1/4 in*
Length	14 in*
Projection	1 23/32 in*
Center to Center Drilling (Spacing)	11 3/4 in*
Edge Distance	2 3/8 in*
Milling Dimension	1/4 in*
Diameter	1 31/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- Flat bar handle of 14 in (356 mm) x 1 1/4 in (32 mm) with projection of 1 11/16 in (43.3 mm) - 2 3/8 in (60 mm) screw for 1 3/8 in (35 mm) to 1 3/4 in (45 mm) door thickness - 2 3/4 in (70 mm) screw for 1 3/4 in (45 mm) to 2 1/8 in (55 mm) door thickness - 1 31/32 in (50 mm) diameter door disc pull - 1 in (25 mm) diameter cap for through bolt

DISCLAIMER

IMPORTANT: Designed for interior wood doors, not suitable for exterior applications. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Pre-drill for through bolts. - Do not overtighten fasteners. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Do not use abrasive cleaners. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

