



Flat Bar Back to Back Door Handles

Product # 246207020290

Color/Finish Black

Material Steel

DESCRIPTION

For swing and sliding doors

Flat Bar Door Handles with through bolt fasteners for back-to-back mounting to a wood door. Includes two sets of through bolt fasteners for various wood door thicknesses: 1 3/8 to 1 3/4 in (35 to 45 mm) and 1 3/4 to 2 1/8 in (45 to 55 mm). Decorative hex head on the through bolt fasteners for the two door pulls for a secure and quick installation. Select from four different finishes that match our collection of Decorative Flat Bar Barn Door Sliding kits in satin brass, brushed stainless steel, matte black, and brushed oil-rubber bronze. See the Suggested Products listed below to explore a list of popular matching Decorative Barn Door Sliding kits and systems. The flat bar pull handle is secure and robust to grip the door to slide or swing open a small to large wood door. Ideal for both residential and commercial interior door applications at the home or office for sliding and swing doors.

ADVANTAGES AND BENEFITS

For a wide range of door thicknesses from 1 3/8 in (35 mm) to 2 1/8 in (55 mm) for back to back mounting. Four different finishes that match and are complementary to the standard selection of barn door sliding systems. Secure grip.

TECHNICAL SPECIFICATIONS

Product #	246207020290
Door Type	Wood
Door Thickness	1 3/8 to 2 5/32 in*
Thickness	1/4 in*
Function	Passage
Usage	Sliding Door, Hinge Door
Screw	Included
Height	14 in*
Width	1 1/4 in*
Projection	1 23/32 in*
Brand	Onward
Center to Center Drilling (Spacing)	11 3/4 in*
Edge Distance	3 15/16 in*
Milling Dimension	1/4 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- 2 flat bar handles of 14 in (356 mm) x 1 1/4 in (32 mm) with projection of 1 11/16 in (43.3 mm) - 2 screws of 60 mm for 1 3/8 in (35 mm) to 1 3/4 in (45 mm) door thickness - 2 screws of 70 mm for 1 3/4 in (45 mm) to 2 1/8 in (55 mm) door thickness

DISCLAIMER

IMPORTANT: Designed for interior wood doors, not suitable for exterior applications. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Pre-drill for through bolts. - Do not overtighten fasteners. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Do not use abrasive cleaners. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

