



NK PAR 25

Product # 253522

DESCRIPTION

Bottom of door not fixed

Each group is hinged to its frame, ensuring perfectly controlled operation.



Characteristics of the door leaves:

- NK PAR. 25:
- Maximum weight: 25 kg (per mechanism, one door with two panels)
 - Maximum dimensions: 60 cm x 240 cm
 - Minimum thickness: 16 mm

Sliding panels are guided by an aluminum track and suspended from an NK roller located at the end of each group. The door leaves hinged to the frame move with European box hinges featuring triple adjustment. The joint between door leaves is constructed with special intermediate Klein hinges, and it is the hinges themselves that maintain the separation of and alignment between the leaves.

REQUIRED PRODUCTS !

Requires ONE of the following products

			Sales unit
	Top Track Product # 4512016 Overall Length: 78 3/4 in*	<div>OR</div>	Length of 2 linear meter
	Top Track Product # 4513461 Overall Length: 9 ft 10 in*		Length of 3 linear meter

TECHNICAL SPECIFICATIONS

Product #	253522
Door Material	Wood
Door Movement	Folding
Track Mounting	Ceiling Mount
Load Capacity	Max. 55 lb
Door Position	Full Overlay
Door Thickness	5/8 to 1 3/8 in*
Roller Type	Axle (Bushing)
Roller Position	Upper
Application	Wardrobe, Pantry, Cabinet, Storage
Brand	Klein
Overall Length	78 3/4 to 118 in*
Drilling	1 3/8 in*
Drilling Depth	15/32 in*
Manufacturing Material	Aluminum
Finish	Mill Finish
Number of Doors	1

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

NK PAR is the perfect system for installing folding closet doors composed of groups of two leaves.

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

