

LAB Recessed Profile

Product # 4122079990

Finish Black

Packaging format Length

DESCRIPTION

Aluminum profile with anti-glare flap for recessed LED installation

- Designed for recessed installation in a blind or through milled groove which is 15/32 in (12 mm) wide and 17/32 in (13 mm) deep
- Light projection is shielded from view and directed away toward the inside of the lit compartment

ADVANTAGES AND BENEFITS

- APEX lens, without dot effect - Customize your lengths as needed; profiles can be cut easily with a miter saw. - Its length can be adapted to your needs with minimum of 11 13/16 in (300 mm) and maximum of 79 in (2 m)

REQUIRED PRODUCTS!

Requires the following products

Sales unit



HE6 PW - FlexyLED 24 V

AND



Lab End Caps Set
Product # 4122990

Bag of 2 units

AND



Lab End Caps Set
Product # 4122990

Bag of 2 units

TECHNICAL SPECIFICATIONS

Product #	4122079990
Mounting	Recessed
Luminaire	Rigid Linear
Location	Inside Cabinet, Under Cabinet, Closet, Furniture
Application	Kitchen, Office, Commercial, Furniture, Closet
Lighting	Ambience, Accent, Task, Functional
Length	78 3/4 in*
Height	1/2 in*
Material	Aluminum
Standards and Certifications	cULus
Function	Aluminum Profile
Lighting Type	LED
Group	LED Group A
Style	Contemporary, Functional
Width	15/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- 78 3/4 in (2 m) Lab LED profile - 78 3/4 in (2 m) polycarbonate Apex LED profile

APPLICATION

- Cabinets - Bookcases - Display cases - Decorative lighting

IMPORTANT INFORMATION

- LED tape light sold separately: only compatible with Flexyled HE6 PW (see Suggested Products) - End caps sold separately - Giuseppe Bavuso design

DISCLAIMER

LED tape light sold separately: only compatible with Flexyled HE6 PW: 166124XX- 166122XX. End caps sold separately.

PRODUCT PHOTOS

