



Painter's Grade Masking Tape 401

Product # 484011855

Width 3/4 in

Rolls per Case 48

DESCRIPTION

3MTM High Performance Green Masking Tape 401/233 is an industrial-strength high performance masking tape used for critical paint masking applications.

- 3M proprietary solvent-free adhesive sticks with superior adhesion to metal, rubber, glass, and plastic while removing cleanly in one piece without residue.
- High-strength green crepe-paper backing conforms to irregular surfaces, resists bleed through from most industrial paint systems, and improves visibility and accuracy during paint masking by creating super-sharp paint lines.
- Temperature use range up to 250 °F (121 °C) for 30 minutes.

ADVANTAGES AND BENEFITS

- Adhesion to steel oz/in (N/100 mm): 36 (39) - Adhesive type: Solvent-free - Backing material: Crepe paper - Color: Green - Elongation: 10% - Length: 60.14 linear yard - Length (metric): 55 linear metre - Maximum operating temperature (Celsius): 121 degree Celsius - Maximum operating temperature (Fahrenheit): 250 degree Fahrenheit
- Performance level: High performance green - Primary liner: Paper - Product category: Masking and duct tapes - Product form: Roll - Tensile strength lb/in (N/100 mm): 25 (438) - Thickness: 6.7 milli-inch (mil) - Thickness (metric): 0.17 millimetre - Time at maximum temperature: 30 minutes.

TECHNICAL SPECIFICATIONS

Product #	484011855
Use	Painter's Grade
Length	180 ft
Thickness	0.00669 in*
Color	Green
Type	Adhesive tapes
Brand	3M

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

PRODUCT PHOTOS

