

110° CLIP top BLUMOTION Hinge

Product # 71B379180

Door Position Inset

Fixing Type Inserta

Screw/Nail Not Included

Packaging Specifications Industrial Packaging

Packaging format Per unit

DESCRIPTION

Integrated BLUMOTION

Precise movement, like clockwork. Integrated BLUMOTION is a technical masterpiece that fits into the smallest of spaces and provides your furniture doors with silent, effortless closing.

CLIP top BLUMOTION is designed to open and close at least 200,000 times, with a compelling quality of motion, to last the lifetime of the furniture.

ADVANTAGES AND BENEFITS

- Innovative technology concentrated into the smallest space, with BLUMOTION integrated into the hinge cup.
- Silent, effortless closing action provides every door with inspiringly perfect motion.
- Effortless closing even for small doors; Blumotion can optionally be deactivated.
- Elegant design for a high-quality look, with compelling technology in a stylish body.
- All-metal hinge, nickel-plated.
- Convenient spiral-tech depth adjustment.
- Compatible with existing mounting plates.
- Features spring closing mechanism.
- Tool-free door-to-cabinet assembly and removal.
- 3-dimensional adjustment with the appropriate mounting plate.
- Features Inserta tool-free cup installation.



REQUIRED PRODUCTS

Requires ONE of the following products

Sales unit



Mounting Plate with Horizontal Cam

Product # 177H310E180

OR



BLUM Inserta Mounting Plate

Product # 174E710180

OR



BLUM Mounting Plate

Product # 174E610180

OR



BLUM Mounting Plates with Adjusting Cam

Product # 174H710180

TECHNICAL SPECIFICATIONS

Product #	71B379180
Use Type	Standard Door
Cabinet Type	Frameless
Finish	Nickel
Closing Mechanism	Self-Closing
Cabinet Thickness	Min. 19/32 in*
Door Thickness	Min. 19/32 in*
Hinge Type	CLIP top BLUMOTION
Milling Depth	1/2 in*
Milling Diameter	1 3/8 in*
Hinge Opening Angle	+110°
Closing Mechanism	Soft-Closing
Material	Steel

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- Do not use a hammer to insert the hinge into the drilled hole. - CLIP top BLUMOTION hinges should be operated within the temperature range of 18 °C and 28 °C to ensure optimal functioning. - Because BLUMOTION function now comes integrated with the hinge, additional assembly processes are no longer necessary after the installation is completed. - For drilling on melamine 5/8, please use the item M01ZB3502, a drill bit shape without tip. *** For a greater selection of mounting plates, please refer to the BLUM mounting plates section ***

APPLICATION

- For the installation of a door on a piece of furniture and/or a cabinet. - Blum hinges are not made of stainless steel, therefore it is not recommended to use them for outdoor applications.

PRODUCT PHOTOS



