



## EVO Hardware Sets

**Product #** 8912695140

**Finish** Chrome (140)

**Load Capacity** 88.2 to 132 lb\*

### DESCRIPTION

#### For wood and glass doors

The EVO barn door style hardware sets for wood and glass doors for three different weight capacity categories: 88 lb (40 kg), 132 lb (60 kg), and 176 lb (80 kg).

#### Features:

- For wood doors 3/4 in (19 mm) to 1 3/8 in (36 mm) thick
- For glass doors 5/16 in (8 mm) to 1/2 in (13 mm) thick
- Available in four finishes: black, chrome, champagne, and titanium
- Includes two soft-close mechanisms, can be adjusted to different positions
- Smooth operating
- Simple, flexible, and low-cost installation

Ideal solution for residential and commercial applications for thin and thick doors, closets and pantries, and access doors for washrooms, bedrooms, and offices.

### ADVANTAGES AND BENEFITS

- A variety of soft-close options that can be adjusted to different positions - Four different finishes

## TECHNICAL SPECIFICATIONS

Product #	8912695140
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Roller Position	Upper
Door Installation	Top Hung
Running Track Fixing	Bracket
Packaging Format	Box
Door Projection	3 5/32 in*
Manufacturing Material	Aluminum
Roller Type	Ball Bearing
Product type	Hardware Set
Door Material	Wood, Glass
Number of Doors	1
Door Width	27 1/2 to 48 in*
Track Mounting	Wall Mount
Door Thickness	5/16 to 1 13/32 in*
Door Height	Max. 8 ft 6 in*
Soft-Closing	Yes
Height Clearance	7 17/32 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

- 2 upper trolleys with fasteners for wood and glass doors - 2 stoppers - 2 soft-close mechanisms - 2 spacer blocks for glass - 1 floor guide for wood - 1 floor guide for glass - Screws and fasteners for individual components only

## IMPORTANT INFORMATION

- Please make sure to read the entirety of the installation manual before proceeding with the installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

## APPLICATION

- For wood and glass doors

## DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

## PRODUCT PHOTOS



