



EVO Track Set

Product # 89127C410140

Overall Length 13 ft 1 in*

Finish Chrome (140)

Door Width 27 1/2 to 48 in*

DESCRIPTION

Adjustable support bracket mounts

The EVO Track Set with bracket mounts for three different weight capacity categories: 88 lb (40 kg), 132 lb (60 kg), and 176 lb (80 kg) each.

Features:

- For wood doors 3/4 in (19 mm) to 1 3/8 in (36 mm) thick
- For glass doors 5/16 in (8 mm) to 3/8 in (10 mm) thick
- Available in four finishes: black, chrome, champagne, and titanium
- Available in three different lengths: 78 3/4 in (2 m), 118 in (3 m), and 156 in (4 m)
- For concealed soft-close mechanisms that can be adjusted to different positions
- Bracket mounts can be adjusted to different positions behind the track
- Smooth operating

ADVANTAGES AND BENEFITS

- Can be installed with concealed soft-close mechanism and adjusted to different positions
- Bracket mounts can be adjusted to different positions behind the track
- Four different finishes

TECHNICAL SPECIFICATIONS

Product #	89127C410140
Track type	Flat oval
Style	Contemporary
Door Installation	Side Mount
Running Track Fixing	Bracket
Packaging Format	Bag
Load Capacity	Max. 176 lb*
Manufacturing Material	Aluminum
Track Mounting	Wall Mount
Soft-Closing	Sold Separately
Door Material	Wood, Glass
Door Movement	Straight Sliding
Door Thickness	5/16 to 1 13/32 in*
Product type	Running and Guiding Tracks
Height Clearance	7 17/32 in*
Door Height	Max. 8 ft 6 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- Aluminum running track - 2 end caps - Wall mount support brackets (wall fasteners not included): - Qty 4 for 2 m - Qty 5 for 3 m - Qty 7 for 4 m - Screws and fasteners for individual components only

IMPORTANT INFORMATION

- Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

APPLICATION

- For wood and glass doors

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS



