



Silo Sliding Door System

Product # 8916604170

DESCRIPTION

Strap mount with solid running rail for wood doors

The Silo strap mount sliding door hardware provides a functional, versatile and secure sliding door solution with a chic look!

The rail connector inserts just over an inch into the solid running rail rod ensuring stability and allowing for a virtually seamless sliding operation.

A sure-fire easy installation with fixation points pre-drilled in the running rail for 16" centers.

As opposed to being mounted on brackets, the system is affixed directly to the wall through the running rail with the combination of spacing sleeves and our lift-locking pin. It therefore eliminates the risk of your door shifting or coming off the track, rendering your space safe for all.

ADVANTAGES AND BENEFITS

- Pre-drilled running rails for 16" centers. - Full rod and connectors ensure added stability.

REQUIRED PRODUCTS

Requires the following products

Sales unit



Fastener Screw Set for Barn Door Systems

Product # 89M6X120A170

Bag of 8 units

TECHNICAL SPECIFICATIONS

Product #	8916604170
Door Material	Wood
Track Mounting	Wall Mount
Load Capacity	Max. 176 lb*
Door Position	In Front of Wall
Door Thickness	1 3/8 to 1 25/32 in*
Roller Type	Ball Bearing
Roller Position	Upper
Application	Standard Access Door, Barn Door
Brand	Richelieu
Overall Length	67 7/8 in
Track type	Tube
Manufacturing Material	Stainless Steel
Finish	Stainless Steel (170), Stainless Steel
Style	Contemporary
Groove Needed for Guiding System	Yes
Number of Doors	1
Door Width	28 to 34 in

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Hotel room, bedroom, office.

IMPORTANT INFORMATION

With custom spacing sleeves 11 mm to 32 mm long, your door can be mounted at various distances from the wall to allow enough space for framing, moldings, etc. Designed for wood doors, weighing up to 176 lb. (80 kg) when installed in the position closest to the wall. The use of a laser level or a minimum 4' spirit level is recommended. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

