



## **HAWA-Aperto 40/F Sliding System for Parallel Stacking of Cabinet Front Doors**

**Product # 8917797**

### **DESCRIPTION**

**Holds up to 7 cabinet front doors in each space.**

HAWA-Aperto 40/F lets cabinet fronts to be stacked out of sight behind a hinged door or used as visible design elements while stationary.

This sliding door hardware system is suitable for multi-door cabinet fronts weighing up to 40 kg (88 lb) that can be stacked out of sight in a niche or cabinet compartment. Be sure to order a 8917797 set per sliding door, as each set is designed for one door only. When closed, the cabinet front is flush, with uniform gaps between panels if desired, even in combination with hinged doors on upper and lower cabinets.

### **ADVANTAGES AND BENEFITS**


With this sophisticated system, the same hardware kit may be used for left and right-hand stacking areas. The number and width of door panels is also flexible. -

Unrestricted access to the entire cabinet width while the front is open. - The system accommodates up to 7 panels per stacking area. - Easy sliding action thanks to a forced guiding system, plastic rollers and anodized aluminum top tracks for light and quiet running. No more trouble with locking sliding panels with this system: just locking the hinged door secures the entire cabinet front.

## REQUIRED PRODUCTS

Requires the following products

Sales unit



**BLUM Mounting Plates with Adjusting Cam**  
Product # 173H710180

AND



**Modular Parallel Track and Guide Set**  
Product # 8917798

Box

Requires ONE of the following products

Sales unit



**Track and Guide Set for HAWA Aperto 40F**  
Product # 891825010  
Overall Length: 98 3/8 in\*

Box

OR



**Track and Guide Set for HAWA Aperto 40F**  
Product # 891825110  
Overall Length: 11 ft 5 in\*

Box

Requires ONE of the following products

Sales unit



**CLIP top BLUMOTION Hinge for Thick Doors**  
Product # 71B979180

OR



**CLIP top Hinge - 95° for Thick Doors**  
Product # 71T975180

## TECHNICAL SPECIFICATIONS

Product #	8917797
Door Material	Wood
Door Movement	Coplanar
Load Capacity	Max. 88.2 lb*
Door Position	Inset/Inlay
Door Thickness	3/4 to 31/32 in*
Roller Type	Premium Ball Bearing
Roller Position	Upper
Application	Wardrobe, Pantry, Furniture, Storage
Brand	Hawa
Number of Doors	2 - 7
Overall Length	98 3/8 to 138 in*
Door Height	8 ft 6 in*
Adjustable	Yes
Opening	Left and Right-Hand Opening
Manufacturing Material	Aluminum
Displayed in These Showrooms	Montreal
Finish	Satin Aluminum
Door Width	15 3/4 to 35 3/8 in*
Cabinet Width	Max. 24 ft 7 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

All types of furniture with high-use doors such as media walls, office cabinets, shop installations, countertop-to-ceiling shutters, kitchenettes, and everywhere that calls for door opening in a reduced space.

## IMPORTANT INFORMATION

- Maximum panel weight: 40 kg (88 lb) - Panel thickness: 19-25 mm (3/4"-1") - Maximum panel height: 2600 mm (approx. 102.4") - Panel width: 400-900 mm (approx. 15.7" to 35.4") - Continuous height adjustment:  $\pm 2$  mm (5/64") - Minimum axis radius: 2,000 mm for curved applications - Center stop with adjustable friction - Flush-mounted panels - Stacking area accommodates up to 7 door panels. However, to avoid damage, we recommend individually sliding each panel into the stacking area. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS

