



HAWA-Junior 40/B Hardware Set with Track Stoppers

Product # 8926039

DESCRIPTION

The HAWA-Junior 40/B is a standard straight sliding system for wood doors weighing up to 88 lb (40 kg) each.

- Low profile rebate/mortise mount suspension plate for the top of the door
- Integrated track stopper with adjustable retaining device to resist door bounce back
- Smooth and quiet premium performance trolleys

TECHNICAL SPECIFICATIONS

Product #	8926039
Load Capacity	88.2 lb*
Product type	Hardware Set
Door Material	Wood
Brand	Hawa
Application	Standard Access Door

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

Pictures provided for visual reference only: actual product may vary. All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantity listed in your order are correct before proceeding to checkout. Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. The documentation, drawings and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. Installation of the Product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. Always remove debris / dust / residues (sawdust and / or aluminum) from the rails using a dry cloth before installing carriage bearings. Never spray lubricant.

