

HAWA PORTA 60 HM Hardware Set

Product # 893133072

DESCRIPTION

Concealed hardware

The HAWA PORTA 60 HM Hardware Set is designed for a single sliding wood door with a weight capacity of up to 132 lb (60 kg).

Features:

- Concealed rebate mount suspension plate
- Track stoppers with adjustable retaining device
- Floor mounted guide wheel
- Optional soft-close mechanisms available for doors from 88 lb (40 kg) to 132 lb (60 kg), sold separately
- Simple and flexible installation
- Smooth operation

IMPORTANT: Use metric dimensions for greater accuracy during installation. Cut a groove of 1/2 in (12 mm) x 5/8 in (16 mm) at the bottom of the door for bottom guide.



TECHNICAL SPECIFICATIONS

Product #	893133072
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Door Position	Full Overlay
Roller Position	Upper
Door Installation	Top Hung
Stopper	Two
Depth	29/32 in*
Adjustable	Yes
Load Capacity	66.1 to 132 lb*
Drilling Depth	23/32 in*
Product type	Hardware Set
Door Material	Wood
Number of Doors	1
Door Width	23 5/8 to 63 in*
Door Thickness	1 9/16 in*
Door Height	31 1/2 to 106 in*
Brand	Hawa

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- 2 upper wheels with suspension bolts - 2 plastic suspension holders - 2 steel housings for suspension holder - 2 stops - 1 floor guide - Screws and fasteners for individual components only

IMPORTANT INFORMATION

IMPORTANT: Use metric dimensions for greater accuracy during installation. - Cut a groove of 1/2 in (12 mm) x 5/8 in (16 mm) at the bottom of the door for bottom guide. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

