

Richelieu's 9W LED Power Supply

Product # 8990

DESCRIPTION

Class II

Input: 110V ~ 240V 50/60Hz

Output: 700mA , 1~3 pcsx 3W LED

Primary Cord: SPT-2 200cm with polarized plug.

Secondary Cord: 1007 #20 20cm +:red -:black with 3-pin distributor connected by XH2.5 connectors

Ambient Temp.: -10°C~ +40°Cfull load

Maximum case temp.: 70°C

Operating Humidity: 20%~95% RH non-condensing

Protections: Short-Circuit / Over Heat



REQUIRED PRODUCTS

Requires the following products



Richelieu's 3 W LED

AND



Richelieu's 3 W LED Series

AND



Richelieu's 3W LED Invoke with Tilt & Swivel

TECHNICAL SPECIFICATIONS

Product #	8990
Lighting Type	LED
Finish	White
Watts	9 W
Standards and Certifications	UL
Length	2 1/2 in
Width	1 1/3 in
Tension (V)	12 V

APPLICATION

* Dry location only

INCLUDED PRODUCT(S)

- 79" power cord

IMPORTANT INFORMATION

Always connect the LED light to the power supply first, and then connect the power supply to the mains. Failure to do so may cause damage to the existing diode. All unused power supply output plugs must have jumpers installed. Do not exceed the maximum wattage by connecting more lights than prescribed; damage to the power supply may result.

DISCLAIMER

Do not cut or splice wiring or the lighting system may be damaged and manufacturer's warranty is voided. The power supply has a polarized plug (one blade is wider than the other) as a safety feature to reduce the risk of electric shock. This plug will fit in a polarized outlet only one way. If the plug does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified technician. Never use an extension cord unless the plug can be fully inserted. Do not alter the plug.

PRODUCT PHOTOS

