



BRIDGE 500 KIT for Aluminum Framed Sliding Doors

Product # 89K4072DR210

Number of Doors 2

Overall Length 78 3/4 in*

Door Height 94 1/2 in*

Soft-Closing No

Finish Satin Finish Aluminum

Packaging format Length

DESCRIPTION

Easy assembly and installation

The Bridge 500 bypassing aluminium frame door kit is a bottom-running sliding door system for doors weighing up to 60 kg (132 lbs) per door. Available in two finishes: Silver Anodized and Satin Black.

The kits include easy to assemble knock-down aluminium frame profiles with one horizontal divider. Maximum door size 1000 X 2400 mm (39-3/8 X 94-1/2 in).

The aluminium frame profiles are designed to work with 4 - 6 mm (3/16 - 1/4 in) thick glass with standard gasket or up to 10 mm (3/8") wood panels without a gasket. The aluminum frame profiles can be cut to suit the desired door sizes.

Select from Kits for two doors with 2.0 m (78-3/4 in) double upper tracks or three doors with 3.0 m (118 in) triple tracks. All tracks are surface mounted.

Includes pull handle.

Three-door kits include locator device for the middle door.

Optional soft-close with adjustable spring.

Important: Use metric dimensions for greater accuracy during installation.

TECHNICAL SPECIFICATIONS

Product #	89K4072DR210
Door Material	Aluminum/Metal Frame, Glass
Door Movement	Straight Sliding
Detailed Door Movement	Bypassing
Track Mounting	Floor Mount
Load Capacity	44.1 to 132 lb*
Door Position	Inset/Inlay
Roller Position	Lower
Application	Closet and Walk-In Closet, Wardrobe, Pantry, Storage
Brand	Pozzi
Door Installation	Bottom Running
Adjustable	Yes
Product type	Complete Set
Door Width	39 3/8 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- THE USE OF SAFETY GLASSES IS RECOMMENDED. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS





