



## Pro Series Albergo Track Set with Integrated Soft-Close

**Product #** 89TY047N2470

**Overall Length** 94 7/8 in\*

**Load Capacity** 132 to 176 lb\*

**Door Width** 39 3/8 to 50 in\*

### DESCRIPTION

#### Direct wall mounts

The Pro Series Albergo track set with two integrated soft-close mechanisms is designed for one wood door. The track is compatible with Pro Series Albergo Strap Mount and Top Mount sliding barn door systems.

Features:

- Pre-drilled track for wall mounts
- Matching 1/4 in (6 mm) discs to be used as shims
- 5 1/8 in (130 mm) fastener screws and collars for secure mounting
- Rail Connector sold separately to join tracks.
- Two soft-close mechanisms pre-assembled in the track

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	89TY047N2470
<b>Detailed Door Movement</b>	Single sliding
<b>Track type</b>	Tube
<b>Diameter</b>	31/32 in*
<b>Style</b>	Contemporary
<b>Manufacturing Material</b>	Stainless Steel
<b>Track Mounting</b>	Wall Mount
<b>Finish</b>	Stainless Steel (170)
<b>Soft-Closing</b>	Yes
<b>Number of Doors</b>	1
<b>Door Movement</b>	Straight Sliding
<b>Product type</b>	Running and Guiding Tracks
<b>Brand</b>	Richelieu
<b>Application</b>	Barn Door

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

- 1 Pre-drilled round track - 2 Soft-close mechanisms, preassembled - Wall-mount stand-offs - 6 mm x 50 mm (1/4 in x 2 in) shims - 130 mm (5 1/8 in) fastener screws and collars

## IMPORTANT INFORMATION

IMPORTANT: Use metric dimensions for greater accuracy during installation. - Please read the entire installation manual before proceeding with installation. - Wear safety gear such as gloves, safety glasses, safety shoes and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residue (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure.

## PRODUCT PHOTOS

