



## NuFlex® 130 Acrylic Painter's Caulk

**Product #** 94150030

### DESCRIPTION

#### Silicone Free Latex Caulk

NuFlex® 130 acrylic painter's caulk and trim seal is an economy-priced caulking material ideally suited for interior and exterior caulking and sealing applications. When exposed to the atmosphere, cures to form a continuous seal. This excellent all-purpose sealant is designed for cracks and joints and adheres to a full range of construction substrates including wood, concrete, metal, glass, stone, brick, stucco and marble. Also recommended for sealing interior joints between walls and panels, around door frames and baseboards, and joints between bathroom fixtures and walls.

### ADVANTAGES AND BENEFITS

- Paintable within minutes. - Matte finish. - Ideal for repairing nail holes in drywall. - Ideal for perimeter trim sealing.

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	94150030
<b>Recommended Use</b>	Interior, Exterior, Non-oiled Wood, Particleboard, Metal, Glass, Door and Window, Construction Grade, Concrete
<b>Finish/Color</b>	Off White
<b>Color on Application</b>	White
<b>Base</b>	Acrylic Latex Polymer
<b>Volume</b>	10.1 oz*
<b>Packaging Specifications</b>	Plastic Cartridge
<b>Weight</b>	10.1 oz
<b>Brand</b>	Nuco
<b>Features</b>	Solvent Resistant, Weatherproof, Superior Bond, Non-Sag, Paintable
<b>VOC Concentration (EPA Method 24)</b>	246 grams per liter
<b>Standards and Certifications</b>	ASTM C834

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

### APPLICATION

Will fill cracks and joints up to 25.4 mm (1 ") wide by 12.7 mm (1/2" ) deep in a single application. Also excellent for filling imperfect mitres on window and door trims to be painted, giving a more professional look to the finished job. Cures to a rubbery seal that withstands joint movement of 24%, 12% compression, 12% extension.

## IMPORTANT INFORMATION

Shelf life and storage: Shelf life is 12 months from date of shipment when stored in a clean, dry area with temperatures between 4 °C to 32 °C (40 °F to 90 °F). Avoid repeated freezing and thawing of sealant while still in the cartridge. For best results, keep sealant in tightly closed container when not in use. Exclusion from responsibility: The preceding information as well as any technical recommendation given in writing, verbally or based on tests are provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are effected according to our most updated General Sales and Delivery Conditions.

## PRODUCT PHOTOS

