



Industrial Sintered Iron Caster

Product # F24834

Load Capacity Per Caster Max. 254 lb*

Wheel Diameter 4 1/32 in*

Total Height 4 31/32 in*

Tread Width 1 5/16 in*

Fastening Type Fixed

Axle Diameter 7/16 in*

Axle Length 2 in*

Mounting Hole Diameter 13/32 in*

Mounting Plate Dimensions 3 1/32 in x 6 1/8 in (77 mm x 156 mm)

DESCRIPTION

High capacity and durability

Industrial sintered iron caster. Recommended for concrete, steel, and asphalt. Heavy-duty, available in two heights.

ADVANTAGES AND BENEFITS

- Non-marking rubber tread - High capacity and durability: Ideal for extreme operating temperatures - Powered iron, compacted and sintered to cast-iron strength, makes smooth tread - Corrosion-resistant zinc finish

TECHNICAL SPECIFICATIONS

Product #	F24834
Mounting Type	Plate
Material	Sintered Iron
Recommended Surfaces	Concrete, Steel, Asphalt
Finish	Metal
Conditions	Extreme Cold, Extreme Heat, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the line art and technical documents. Not recommended for applications in areas with high humidity.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

