



## Industrial Black Phenolic Casters

**Product #** F27116

**Load Capacity Per Caster** Max. 772 lb\*

**Wheel Diameter** 5 31/32 in\*

**Total Height** 7 5/16 in\*

**Tread Width** 1 25/32 in\*

**Fastening Type** Fixed

**Axle Diameter** 5/8 in\*

**Axle Length** 1 31/32 in\*

**Features** Without Lubrication Fittings

### DESCRIPTION

#### Non-marking rubber tread

These heavy-duty industrial black phenolic casters are suitable for extreme cold and extreme heat conditions. Available in fixed, swivel, or swivel with brake.

### ADVANTAGES AND BENEFITS

- Non-marking, non-conductive, and spark-proof - High strength, high impact, resistance to oil, gasoline, and dilute acids - Carbon steel top plate, heat-treated for extra strength - Lubrication fitting for swivel raceway and wheel bearings

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	F27116
<b>Mounting Type</b>	Plate
<b>Material</b>	Phenolic
<b>Recommended Surfaces</b>	Concrete, Carpet, Wood/Planking, Asphalt
<b>Finish</b>	Black
<b>Mounting Hole Diameter</b>	7/16 in*
<b>Mounting Plate Dimensions</b>	31 5/16 in x 4 1/2 in (100 mm x 115 mm)
<b>Conditions</b>	Extreme Cold, Extreme Heat, Petroleum Products, Dilute Acids

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

### IMPORTANT INFORMATION

For all additional measurements, please see the technical documents

## DISCLAIMER

Technical data subject to change without prior notice.

## PRODUCT PHOTOS

