



Sivosat Self-Sealing Polyurethane Clear Topcoat

Product # FLFA15325

DESCRIPTION

This product has good coverage, flow, surface hardness and is fast drying. Versatility of use; suitable for spray and curtain-coater when properly diluted. The self-sealing property makes it ideal for open pore applications.

REQUIRED PRODUCTS

oz*

Requires ONE of the following products Sales unit LCB195 Non-Yellowing Catalyst Product # FLCB19505 Volume: 169 oz* OR LCB195 Non-Yellowing Catalyst Product # FLCB195125 Volume: 423 oz* OR LCB185 Catalyst for Polyurethane Product # FLCB18505 Volume: 169 oz* OR) LCB185 Catalyst for Polyurethane Product # FLCB185125 Volume: 423



TECHNICAL SPECIFICATIONS

Product #	FLFA15325
Volume	52.8 pt*
Category	Lacquers
Туре	Sivosat
Color	Clear
Finish	Low Satin
Gloss Level	30
Brand	SIVAM
Application Surface	Wood
Technology/Base	Polyurethane
Application Method	Airmix Spray, Airless Spray, Curtain Coater
Vehicle	Solvent Based

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

APPLICATION

For cabinets, furniture, furnishing equipment, furniture components, frames, baseboards, doors and different wood substrates.

PRODUCT PHOTOS

