



CONTURO KA 65 Hand-Held Edgebander Set

Product # FS574616

DESCRIPTION

With the new CONTURO Edgebander, it's just just as easy to apply edgebanding on the job site as it is in the shop. Even if you have a large stationary edgebanding machine, the CONTURO can complement your edgebanding process by giving you a way to work with radii, circular pieces, bevels and small pieces.

The CONTURO's offers exceptional ergonomic design, including dual speeds, and a unique patented hot melt glue adhesive system. There's no risk of burns because the glue system is thermally isolated.

Ditch the iron or hot air gun to and gain the benefits of a dedicated edgebanding machine without the cost associated with stationary equipment.

ADVANTAGES AND BENEFITS

-Inexpensive compared to alternatives like stationary edge banding machines -Capable of edge banding curves, circles, convex and concave radii and inside corners - Electronically controlled precision glue distribution system for maximum adhesion - Compact, portable, ergonomic design for easy use and flexibility -Optional table mounting for working with small pieces

REQUIRED PRODUCTS

Requires the following products



EVA Edgebanding Adhesive

TECHNICAL SPECIFICATIONS

Product #	FS574616
Brand	Festool
Type of Tool	Electric

APPLICATION

Suitable for machining all types of wood, plastic or melamine edging.

INCLUDED PRODUCT(S)

Kit includes: - 1 support handle and 1 guide table - 1 batch of 4 Natural color EVA Adhesives (FS499812) - 1 Systainer T-LOC SYS 4 - Edge Bander Trimming Set SYS KB-KA 65



IMPORTANT INFORMATION

Specifications: Power consumption: 1200watts/10amps, 120V AC Heating Time: 8-10min. Melting Temperature: 212-410F (100-210C) Infeed Speed: 6.5/13.1 ft/min (2/4 m/min) Inner Radius:- Minimum of 2" (50mm) Max. Banding Height: 23/32" to 2-9/16" (18-65mm) Max. Banding Thickness: 1/32" to 1/8" (0.5-3.0mm) Weight: 17.4 lbs (7.9 kg.)

PRODUCT PHOTOS























