



Jowacoll 114.60 Dowel Driving Glue

Product # JW11460

DESCRIPTION

Specifically designed PVA glue for low-pressure models from manufacturers Koch, Hoffmann, Lehbrink, Weeke and Accu Systems.

ADVANTAGES AND BENEFITS

- Very low viscosity - Moderate to long setting speed which contains a UV indicator - Special additives will prevent nozzles from clogging

TECHNICAL SPECIFICATIONS

| Product # | JW11460 |
|-----------------------------------|--|
| Recommended Use | Interior, Dowel Glue |
| Color Before Application | White |
| Dried Film | Clear |
| Viscosity | 125 cps |
| Weight | 45 lb |
| Brand | Jowat |
| Features | Fluorescent, Slow Drying |
| VOC Concentration (EPA Method 24) | 0 grams per liter |
| Solid Content (Approx.) | 40% |
| Base | Polyvinyl Acetate Emulsion, Specialized Vinyl Acetate Emulsion |
| pH | 5.0 |
| Freeze/Thaw Stability | Unstable |

APPLICATION

For automatic dowel-driving equipment operating at a low pressure of approximately 5-8 bar (70-120 psi).

IMPORTANT INFORMATION

Due to the relatively slow set speed, further processing of glued parts should not take place earlier than three hours after application.



PRODUCT PHOTOS

