



## Jowatherm 288.7 Granular Hot Melt Adhesive

**Product #** JW2887044

### DESCRIPTION

Low-viscosity hot melt with fast melting properties, good heat resistance, and good adhesion and bond stability at low temperatures.

### ADVANTAGES AND BENEFITS

- Good heat resistance - Good adhesion and bonding - Stable at low temperatures - High oxidation and color stability - Good wetting and adhesion properties

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	JW2887044
<b>Type</b>	Granular
<b>Line speed ( /minute)</b>	39 ft 4 in to 131 ft*
<b>Filler Agent</b>	With
<b>Adhesive for use with</b>	Thin PVC and ABS edgbanding, Thick PVC and ABS edgebanding, Solid wood edgebanding, Multi-layered 1, 1.5, 2, 3 mm edgebanding, Backed thin wood edgebanding, Laminate, Resin-embedded paper, Veneer edgebanding
<b>Finish/Color</b>	Beige
<b>Working Temperature</b>	180 °C to 200 °C
<b>Weight</b>	44 lb
<b>Brand</b>	Jowat
<b>Base</b>	Ethylene Vinyl Acetate

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Suitable for: - Veneer - Solid wood - Resinated paper - PVC and ABS - Primed HPL - Pre-coating and soft-forming applications

## IMPORTANT INFORMATION

It is highly recommended to consult your sales representative or a technical expert before purchasing a new edgebanding glue.

## PRODUCT PHOTOS

---

