



Eurolinx 12 V dc

Product # LEUL4W273WAL

Light Color Warm White

Kelvin Color Temperature (K) 3000 K

Length 10.75 in

Watts 4 W

Packaging format Per unit

DESCRIPTION

Luniform output

The Eurolinx flat profile blends in with any application. Using specialized diffuser and reflector technology to achieve Luniform output, this European styled light is a perfect choice for all contemporary and high-end commercial applications. Use the magnets within the U-Clips for metal shelving or office furniture mounting. At 4 W per foot and over 200 lumens, Eurolinx is a top pick for high illumination.

ADVANTAGES AND BENEFITS

- Optional inline gradual dimmer.
- Mounting clips with integrated magnets allow for metal surface mounting as well as traditional screw mounting.
- Linkable (back-to-back or link cord) up to 10' (3 m) continuous run.
- Sleek, contemporary European design.
- Two beam spreads based on orientation.
- Dimmable.
- Luniform technology.
- Available in four lengths.

REQUIRED PRODUCTS

Requires ONE of the following products



EquiLine Power Supplies

OR



TRESKO 12 V Dimmable LED Hardwire Power Supply

OR



TRESKO 12 V LED Plug-In Power Supply

OR



TRESKO EquiLine 12 V LED Plug-In Power Supply

OR



TRESKO 12 V Dimmable Hardwire Power Supply

TECHNICAL SPECIFICATIONS

Product #	LEUL4W273WAL
Location	Furniture
Application	Kitchen, Living Room
Mounting	Surface
Luminaire	Rigid Linear
Lighting	Task
Finish	Aluminum
Standards and Certifications	UL
Height	0.3 in
Lighting Type	LED
Tension (V)	12 V
Features	Dimmable

APPLICATION

- Cabinets or shelving - Countertops - Showcases

INCLUDED PRODUCT(S)

Each light includes 79" (2 m) cord, U-Clips, back to back connector.

IMPORTANT INFORMATION

4W/ft. (13.1 W/m) 216 per ft. (708 per m) Average Rated Life: 30,000 Hours Max Per 60W Power Supply: 15' (4.6 m) Max Continuous Run: 10' (3 m)

DISCLAIMER

All product dimensions and specifications are subject to change without prior notice. Commercial grade - 3 year warranty offered by manufacturer. IES data verified by Intertek testing lab.

PRODUCT PHOTOS

