Pockit® 120-M (non linking)

Product # LMPOC4W120NLCBL

Finish Black

Light Color Cool White

Kelvin Color Temperature (K) 5000 K

DESCRIPTION

The smaller size rivals standard "puck" style light fixtures but produces 25% more light output than traditional halogen and xenon puck lights.
Each fixture has a built-in dimmable driver and the commercial grade, all-metal construction provides for optimal heat sinking.

ADVANTAGES AND BENEFITS

Easy and quick installation -- no electrician required True plug & play: No transformer or power supply required

REQUIRED PRODUCTS

Requires the following products

Pockit® 120-M Starter Cord

TECHNICAL SPECIFICATIONS

Product #	LMPOC4W120NLCBL
Location	Under Cabinet
Application	Kitchen, Living Room, Commercial
Mounting	Recessed, Surface
Luminaire	Fixed Spots
Lighting	Accent, Task
Standards and Certifications	UL
Height	7/8 in*
Diameter	2 3/4 in*
Bore Hole	2 3/8 in*
Lighting Type	LED
Tension (V)	120 V
Watts	4 W
Price Point	Optimum
Features	Dimmable

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, click here.

APPLICATION

- Displays - Task lighting/flood lighting - Interior cabinets/shelving - Under cabinets

INCLUDED PRODUCT(S)

All Pockit® lights can be either surface-mounted or recess-mounted. Surface mount ring included with each light. Power cord required. Sold separately (8' length available in black or white)

IMPORTANT INFORMATION

- 4W 120V - Dimmable to 50% by standard LED wall dimmers. - 30,000 end of life hours. - 2-3/8" (60 mm") hole required for recessing. - Maximum continuous run: 15 fixtures

DISCLAIMER

Product shown is for visual reference All product dimensions and specifications are subject to change without prior notice.

PRODUCT PHOTOS

Dimensions:
Actual Size

Front

2-3/8"
(60 mm)

9"
(229 mm)

Side

7/8"
(22 mm)

2-3/8"
(60 mm)

Mounting Ring

7/8"
(22 mm)

2-3/4"
(70 mm)