



## Non-Dimmable Power Supply 24 V

**Product #** NDH24396

**Maximum Fixtures per Driver** 96

**Power Supply** 3 x 96 W

**Output Port** 30 ports

### DESCRIPTION

Non-dimmable LED power supply with added 12 in (304.8 mm) output micro connection distributor. For more connections, please see 24 V hubs and micro adapters in the Suggested Products section.

Note : These power sources are exclusively hardwire

## REQUIRED PRODUCTS

Requires the following products

**Sales unit**



### SMART BTRF LED Receiver

Product # BTRF24961248

Requires ONE of the following products

**Sales unit**



### SMART BTRF 2-ZONE Kinetic Power

Product # RFDE2802Z

OR



### SMART BTRF 1-ZONE Kinetic Power

Product # RFDE2801Z

OR



### SMART BTRF Switch

Product # RFD9001Z

## TECHNICAL SPECIFICATIONS

Product #	NDH24396
Lighting Type	LED
Compatibility	Micro 24
Finish	White
Standards and Certifications	ETL
Material	Metal
Tension (V)	24 V

## IMPORTANT INFORMATION

- Suitable for dry and damp locations - 90 V ac to 132 V ac - 3 W minimum load \* Maximum fixtures indicates the highest number of connections recommended for an average of 3 W per fixture. Please do not exceed that number. \* Output ports indicates the number of connections permitted by the adapter included in the box. For more fixtures, please see 24 V Micro DC adapter in the Suggested Product section. Please do not exceed the maximum fixtures per driver.

## DISCLAIMER

\* Richelieu is not responsible for damages caused by an overloaded power supply. Please follow Richelieu's recommended wattage listed in the Power Supply field of the Technical Specifications section. \* For interior use only. \* Pictures provided for visual reference only. Actual product may vary.

## PRODUCT PHOTOS

