



High-Temperature, High-Strength Adhesive Spray - LIONGRIP R015

Product # R01511C

Finish/Color Clear Transparent

Weight 11 lb

DESCRIPTION

This glue provides easy, uniform coverage to all types and sizes of surfaces. The canister offers simplicity and portability. This glue is a strong adhesive that ensures excellent contact. Initial tack allows a uniform, high-strength bond under a wide variety of laminating conditions.

ADVANTAGES AND BENEFITS

- OTC qualifies for LEED, NC and CI EQ Credit 4.4: laminating adhesives shall contain no urea formaldehyde resins. - Fast drying - Easy to use - High heat resistance - High performance - Adjustable flow nozzle - Aerosol format features adjustable spray force, other formats adjust the spray force via the spray gun To clean off excess glue, use LIONGRIP cleaner #RS02020L or RCCAR13C.

TECHNICAL SPECIFICATIONS

Product #	R01511C
Packing	Canister
Base	Solvent
Open Time	30 minutes
Dry Time	2 to 3 minutes
VOC Concentration (EPA Method 24)	426 grams per liter
Brand	Liongrip
Standards and Certifications	LEED
Features	High Heat Resistance, Flammable
Coverage Rate	3.0 dry grams/sq. ft. minimum
Flash Point	-104 °C (-155 °F)

APPLICATION

- Particleboard - Laminates - Plywood - Hardwood - Leather - Rubber - Metal

IMPORTANT INFORMATION

Qualifies for LEED®-NC & CI EQ Credit 4.4: laminating adhesives shall contain no urea formaldehyde. LEED®-NC & CI EQ Credit 3.2

PRODUCT PHOTOS

