



High-Performance Adhesive Spray - LIONGRIP R517

Product # R5175480L

Finish/Color Red

Volume 54 gal.

Packaging format Per unit

DESCRIPTION

LIONGRIP R517 is a high-performance adhesive.

ADVANTAGES AND BENEFITS

- Can be postformed - Dries rapidly - High open time - Resistant to high temperatures - Highly resistant to tearing and shearing - Waterproof - Flexible

TECHNICAL SPECIFICATIONS

Product #	R5175480L
Packing	Bulk/Liquid
Base	Neoprene
Open Time	60 minutes
Dry Time	3 to 5 minutes
VOC Concentration (EPA Method 24)	599 grams per liter
Viscosity	175 cps
Recommended Coverage	14.4 m ² /3.78 l (155 sq. ft/gal)
Solids Content (approximate)	18.5%
Brand	Liongrip
Standards and Certifications	LEED
Features	Flammable
Recommended Use	Postforming
Flash Point	-29 °C (-20 °F)

APPLICATION

LIONGRIP R517 high-performance contact cement is an ideal choice for most permanent adhesive applications on a wide variety of substrates. For use with: - Plastic laminate - Decorative laminate - Drywall - Edgebanding - Veneer - Metals (excluding copper) - Wood - Fiberglass - Polyurethane foam - Rigid plastics To clean off excess glue, use LIONGRIP cleaner #RS02020L or RCCAR13C.

IMPORTANT INFORMATION

Qualifies for LEED®-NC & CI EQ Credit 4.4: laminating adhesives shall contain no urea formaldehyde. LEED®-NC & CI EQ Credit 3.2

PRODUCT PHOTOS

