



CS Double and Triple CaviTrack

Product # TSTMT3MF8134

Overall Length 96 in

Width 6 27/64 in

Number of Doors 3

Door Thickness 1 3/4 in

Overall Height 1 15/32 in

DESCRIPTION

For 1 3/8 in and 1 3/4 in (35 mm and 45 mm) doors

CS double and triple CaviTrack ceiling mount tracks for the Door Collection Series.

Features:

- Offered in popular pre-cut lengths for different CS sliding door systems
- Can be surface or recess mounted to the ceiling
- For 1 3/8 in (35 mm) and 1 3/4 in (45 mm) thick doors

ADVANTAGES AND BENEFITS

- Can be surface or recess mounted to the ceiling
- Pre-cut to popular lengths
- Double and triple tracks

TECHNICAL SPECIFICATIONS

Product #	TSTMT3MF8134
Detailed Door Movement	Single sliding
Track type	Box Track
Compatible with	CS Door Collection
Door Installation	Top Hung
Running Track Fixing	Surface and Recessed
Packaging Format	Bulk
Load Capacity	500 lb
Manufacturing Material	Aluminum
Track Mounting	Ceiling Mount
Roller Position	Upper
Door Position	Inset/Inlay
Finish	Anodized, Anodized Aluminum
Door Material	Wood
Pre-drilled	Yes
Door Movement	Straight Sliding, Movable Wall
Product type	Running and Guiding Tracks
Brand	Cavity Sliders

INCLUDED PRODUCT(S)

Track only.

IMPORTANT INFORMATION

Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. Never spray lubricant on this product.

DISCLAIMER

Please make sure to read the entirety of the installation manual before proceeding with the installation. Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. See instructions for rough opening and other dimensions. Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product.

PRODUCT PHOTOS

