





HAWA JUNIOR B Series Sliding Door System

Product # WEBKIT1010599

Detailed Door Movement Single sliding

Load Capacity 223 to 265 lb*

Door Thickness 1 1/2 to 2 1/4 in*

Application Sliding Wall / Standard Access Door

Overall Length 9 ft 10 in*

Soft-Closing Yes

Soft-Close Type Two Soft-close

Number of Doors 1

Door Height 78 3/4 to 157 in*

Door Width 45 1/4 to 60 in*

DESCRIPTION

Mortise mount suspension plate for low headroom applications

The HAWA JUNIOR B Series sliding wood door systems for doors weighing 88 lb to 550 lb (40 kg to 250 kg) per door.

- Low profile rebate/mortise mount suspension plate for the top of the door
- Minimal gap between the top of the door and upper track, does not require a fascia
- Integrated track stopper with adjustable retaining device to resist door bounce back
- Versatile track options in various lengths for single sliding, biparting, and bypassing applications
- Smooth and quiet premium performance and long-lasting trolleys

- Available SoftMove soft/self-closing mechanism sold separately for doors weighing from 88 lb to 264 lb (40 kg to 120 kg) per door

The HAWA JUNIOR B Series is an ideal solution for premium commercial and residential projects, room dividers, pocket doors, wall partitions, and low headroom applications.

ADVANTAGES AND BENEFITS

- Low profile rebate/mortise mount suspension plate - Minimal installation height - Quiet action - Track stopper with adjustable retaining device

INCLUDED IN THIS WEBKIT

Sales unit



Rolling Hardware, with Two Track Stoppers, for Hawa-Junior 120/B System Product # 8926042

Box





HAWA-SoftMove Soft-Close Mechanism Product # 8925988

Pre-Drilled top Track Product # 891486710 Length of 3 linear meter

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1010599
Door Material	Wood
Door Movement	Straight Sliding
Track Mounting	Ceiling Mount
Door Position	Inside Frame
Brand	Hawa
Finish	Satin Aluminum
Adjustable	Yes
Door Installation	Top Hung

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

Box



DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

