



## HAWA-Junior 120/GP Top Hung Sliding System for Glass Doors with Fixed Glass

**Product #** WEBKIT1010844

### DESCRIPTION


#### Top running sliding system for frameless glass doors

The HAWA-Junior 120/GP is a top running sliding system for frameless glass doors with side fixed glass panels, weighing up to 264 lbs (120 kg) each. A special track with a pocket for fixed glass door panels. A great system for laminated glass panels.

### ADVANTAGES AND BENEFITS



- Carriage with 2 plastic wheels - Silent, easy sliding - Track stop with adjustable retainer - Height can be adjusted without lifting the door - Low overall height - Cover plate (various colors, rounded and angled) - Lower guide with specialized chuck for glass sliding doors - Tamper-proof suspension mounted to interior - Compatible with safety glass or laminated safety glass - Easy fitting of fixed glass - Available accessories: SoftMove and SoundEx

### INCLUDED IN THIS WEBKIT

	Sales unit
 <p><b>Partial Set for Single Glass Door</b> Product # 8920492</p>	Box

### REQUIRED PRODUCTS

Requires ONE of the following products

	Sales unit
 <p><b>Rattle-Proof Bottom Guide for 8-10-12-(12.7) mm Glass</b> Product # 8916029100 Finish: Satin Aluminum (VC)</p>	Bag
(OR)	
 <p><b>Rattle-Proof Bottom Guide for 8-10-12-(12.7) mm Glass</b> Product # 8921267170 Finish: Stainless Steel (170)</p>	Bag
(OR)	



### Guide slider, rattle proof, plastic, with mounting screws

Product # 891602090

Bag

OR



### Single bottom guide channel

Product # 891934910

Length of 3.5  
linear meter

OR



### Set of Fixing Parts for Dual Bottom Guide Channel - Set of 5 Pieces

Product # 891916290

Bag of 5 units

OR




### Bottom door stop with centering assembly

Product # 8921473170

Bag

OR



### Self-adhesive sliders 10 mm (25 64 ") glass

Product # 891619311

Bag

OR



### Stop bumper

Product # 89156362G

Bag

OR



### Bottom door stop with centering assembly

Product # 8920773174

Bag

OR



### Bottom Guide Channel, Undrilled

Product # 891540510

Length of 6  
linear meter

## TECHNICAL SPECIFICATIONS

Product #	WEBKIT1010844
Door Material	Glass
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Track Mounting	Ceiling Mount
Load Capacity	Max. 265 lb*
Door Position	Inside Frame
Door Thickness	5/16 to 1/2 in*
Roller Type	Axle (Bushing)
Application	Closet and Walk-In Closet, Movable Glass Wall, Glass Partition, Standard Access Door
Brand	Hawa
Overall Length	19 ft 8 in*
Manufacturing Material	Aluminum
Finish	Satin Aluminum
Number of Doors	1
Door Height	9 ft*
Door Width	48 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Suitable for all environments such as conference rooms, offices, reception desks, hotel pools, gyms, and even for separation between the dining room and kitchen: the possibilities are endless.

## IMPORTANT INFORMATION

For two-panel sliding doors, please order two sets for single doors. For panel widths of 1200 mm (3' 11-1/4") or above, a bottom guide channel/two guide units are recommended. For all required components, please see the technical documents. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS

